

## DS-D5022QE-B 21.5" LED Monitor

### key Features

- LED backlit technology with full HD 1920×1080
- Wide view angle: 170°(H)/160°(V)
- Multiply inputs: HDMI, VGA
- 3D comb filter, 3D De-interlace
- 3D noise reduction
- VESA stand bracket

Model:

DS-D5022QE-B



## DS-D5022QE-B 21.5" LED Monitor



### Specification

Model	DS-D5022QE-B
Display	
Display Type	LED-Backlit
Screen Size	21.5"
Pixel Pitch(H×V)	0.248mm × 0.248mm
Max Resolution	1920×1080
Brightness	250cd/m2 (Typical)
Contrast	1000:1
Response Time	5ms
Color	16.7M
Viewing Angle	Horizontal 170°, Vertical 160°
Interface	
HDMI	1
VGA	1
Mounting	
VESA	100mm × 100mm
General	
Power Supply	100 ~ 240V AC
Consumption	< 30W(on) < 0.4W(Standby)
Operation Temperature	0°C ~ 40 °C
Operating Humidity	10%-85% (No Condensation)
Storage Temperature	-20°C ~ 60°C
Storage Humidity	5%-95% (No Condensation)
Dimension (W×H×D)	511mm×377mm×170mm
Weight	4.5Kg(Gross weight) , 3.3(Net weight)